



INNOVATION. TECHNOLOGY. RELIABILITY.

## TRACK SAFETY LIGHTS COMPARISON CHART

	<b>Model 6752</b> <b>Double Wide &amp; High</b>	<b>Model 6750</b> <b>Double High</b>	<b>Model 6751</b> <b>Premium Height</b>	<b>Model 6770</b> <b>Indoor Tracks</b>
<b>Number of LEDs</b>	1,536 Ultrabright LEDs	768 Ultrabright LEDs	384 Ultrabright LEDs	96 Ultrabright LEDs
<b>Segments</b>	16 segments	8 segments	4 segments	1 segment
<b>LED Colors</b>	4 colors	4 colors	4 colors	4 colors
<b>Power</b>	10-14VDC 2.3A	10-14VDC 1.2A	10-14VDC 0.6A	Internal Battery
<b>Optional Power</b>	110/230VAC Adapter 6757B	110/230VAC Adapter 6757A	110/230VAC Adapter 6757A	
<b>Data Comm</b>	Wireless IP Network RS422/485	Wireless IP Network RS422/485	Wireless IP Network RS422/485	Wireless - -
<b>Dimensions</b>	H: 28.0in (711mm) W: 16.0in (406mm) D: 2.25in (57mm)	H: 28.0in (711mm) W: 9.5in (241mm) D: 2.25in (57mm)	H: 15.25in (387mm) W: 9.5in (241mm) D: 2.25in (57mm)	H: 6.5in (165mm) W: 6.5in (165mm) D: 3.75in (95mm)
<b>Viewable</b>	H: 26.0in (660mm) W: 9.88in (251mm) up to 2,000ft (610m)	H: 26.0in (660mm) W: 5.0in (127mm) up to 1,000ft (305m)	H: 13.25in (337mm) W: 5.0in (127mm) up to 500ft (152m)	H: 3.0in (80mm) W: 5.0in (121mm) up to 150ft (46m)
<b>Mounting</b>	Eight 10-32	Eight 10-32	Four 10-32	Cradle Mount
<b>Optional Pipe mount</b>	Two 6760A	Two 6760A	One 6760A	Pipe/Wall/Pole