



INNOVATION. TECHNOLOGY. RELIABILITY.

T-LINK WIRELESS COMPARISON CHART

Product Name	<u>T-Link</u>	<u>T-Link2</u>	<u>T-Link 3.0</u>
Features			
Wireless Output	100mW	250 mW	250 mW
Status Readout	3 Red LEDs	Red/Green LED	Red/Green LED
Mounting	-	1/4-20 on bottom	Option Mount Pole/Wall/1/4-20
Low Battery Warning	-	Yes	Yes
Low Battery Project	-	Yes	Yes
Performance			
Run Time (Autocross)	44 hours	34 hours	50 hours
Run Time (Drag)	42 hours	39 hours	45 hours
Run Time (Mud Bog)	44 hours	34 hours	50 hours
Full Recharge Time	6 hours (min)	1.5 hours	8 hours (max)
Power Source			
Battery Capacity	60 WH	29 WH	24 WH
Battery Type	Sealed Lead Acid	Lithium-Ion	Removable Battery
Power Protection	Resettable Fuse	Resettable Fuse	Over/Under Charge
Charger	12VDC	9.6VDC	USB cable
Charger Port	2.5mm	2.1mm	on Battery Pack
Enclosure Specs			
Height	5.9in/149.2mm	4.6in/115.9mm	5.2in/115.9mm
Width	6.9in/174.6mm	5.2in/131.8mm	2.8in/131.8mm
Depth	3.1in/77.8mm	2.4in/60.3mm	2.4in/60.3mm
Weight	5.4lbs/2.4kg	1.3lbs/0.6kg	0.8lbs/0.4kg
Comparison to T-Link			
RFOutput Power	-	150% more	150% more
Recharge Time	-	4x faster	Swap Battery Pack
Dimensions	-	55% smaller	55% smaller
Weight	-	76% lighter	90% lighter

NOTE: Results above are lab testing of equal models for comparison of estimated product performance