

RACE AMERICA

INNOVATION. TECHNOLOGY. RELIABILITY.

TRACK SAFETY LIGHTS COMPARISON CHART

	<u>Model 6752</u> <u>Double Wide & High</u>	<u>Model 6750</u> <u>Double High</u>	<u>Model 6751</u> <u>Premium Height</u>	<u>Model 6770</u> <u>Indoor Tracks</u>
Number of LEDs	1,152 Ultrabright LEDs	576 Ultrabright LEDs	288 Ultrabright LEDs	72 Ultrabright LEDs
Segments	16 segments	8 segments	4 segments	1 segment
LED Colors	RGB LED colors	RGB LED colors	RGB LED colors	RGB LED colors
Power	10-14VDC 3.12A	10-14VDC 1.60A	10-14VDC 0.86A	Internal Battery
Optional Power	110/230VAC Adapter 6757B	110/230VAC Adapter 6757A	110/230VAC Adapter 6757A	
Data Comm	Wireless IP Network RS422/485	Wireless IP Network RS422/485	Wireless IP Network RS422/485	Wireless - -
Dimensions	H: 28.0in (711mm) W: 16.0in (406mm) D: 2.25in (57mm)	H: 28.0in (711mm) W: 9.5in (241mm) D: 2.25in (57mm)	H: 15.25in (387mm) W: 9.5in (241mm) D: 2.25in (57mm)	H: 6.5in (165mm) W: 6.5in (165mm) D: 3.75in (95mm)
Viewable	H: 26.0in (660mm) W: 9.88in (251mm) up to 2,000ft (610m)	H: 26.0in (660mm) W: 5.0in (127mm) up to 1,000ft (305m)	H: 13.25in (337mm) W: 5.0in (127mm) up to 500ft (152m)	H: 3.0in (80mm) W: 5.0in (121mm) up to 150ft (46m)
Mounting	Eight 10-32	Eight 10-32	Four 10-32	Cradle Mount
Optional Pipe mount	Two 6760A	Two 6760A	One 6760A	Pipe/Wall/Pole